



DECLARATION OF PERFORMANCE
No. DOP-CPR-ADC-51

1. Unique identification code of the product-type or product family: PAPIER PEINT DECORATIF intissé 110 à 150 gr/m²					
2. Type, batch or serial number or any other element allowing identification of the construction product: papier-peint					
3. Intended uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Use as wall covering(s) within a building according to the manufacturer's specifications and installation practices in accordance with EN 15102:2007+A1:2011					
4. Name, registered trade name or registered trade mark and contact address of the manufacturer: TEXDECOR SAS 2 rue d'Hem 59 780 Willems					
5. Where applicable, name and contact address of the authorised representative (distributor, importer):					
6. System of assessment and verification of constancy of performance of the construction product: AVCP system 4					
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: «system 1» Notified product certification body «name: nbn» performed the determination of the product type on the basis of type testing (including sampling), initial inspection of the manufacturing plant and of factory production control, continuous surveillance, assessment and evaluation of factory production control under system 1 and issued the certificate of constancy of performance: «certificate number». or «system 3» Notified testing laboratory «name: nbn» performed the determination of the product type on the basis of type testing (based on sampling carried out by the manufacturer) and issued the test report(s): «test report number(s)». or «system 4» Not applicable					
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: not applicable					
9. Declared performance:					
Essential characteristic	Performance	Harmonised technical specification	Essential characteristic	Performance	Harmonised technical specification
Reaction to fire EN 13501-1	C-s1,d0	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	<0,2 mg/kg	EN 15102:2007 A1:2011
Release of formaldehyde EN 12149-C	< 120 mg/kg		Sound absorption ISO 354	NPD	
Release of heavy metals EN 12149-B	Antimony < 0.1 mg/kg Arsenic < 0.1 mg/kg Barium < 0.1 mg/kg Cadmium < 0.3 mg/kg Chromium < 0.1 mg/kg Lead < 0.5 mg/kg Mercury < 0.1 mg/kg Selenium < 1 mg/kg		Thermal resistance «EN 12524» or «EN 12667»	NPD	
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by: JANSSENS BENOIT Texdecor – Novembre 2019					
			Benoit JANSSENS Quality Manager Wallpaper & Wallcovering Department 		